

OVTPA

Stock Rules:

5000, 5700, 6700 lbs.

1. Notwithstanding general rule 1, tractors will be 1959 and older
2. Tire size will be maximum 200 square inches (Using NATPA chart 14.9-38 max.) unless tractor came from factory with larger tire size
3. *reserved for future*
4. Radial tires allowed
5. No duals
6. Top Cut Tires allowed
7. 4 mph max speed
8. Maximum engine rpm will be 10% over stock rpm
9. Stock engine components or OE replacement parts
10. Stock engine parts without modifications
11. No MSD type electronic ignition
 - a. Pertronix ignition is allowed
12. No turbo chargers allowed unless factory installed
13. Must have hood, grill, fuel tank and platform that match the model of tractor
 - a. Fenders are mandatory
14. *reserved for future*
15. Pump fuel only, no secondary fuels
16. No weight frame or weight may extend more than 11 feet forward from centre of rear axle. Up to 50% of the added weight will be allowed behind the rear axle, not extending past the outer radius of the tire. No weights behind rear axle if tractor does not have wheelie bars
17. No weights on platform unless fastened; at discretion of tech officials
18. Max 20" drawbar height (18" without wheelie bars), no less than 18" from rear axle center and secure in all directions
19. All tractors that compete at more than two pulls must have wheelie bars that support the weight of the tractor (see rule #12 improved for specs)
20. If a stock competitor continually beats all other stock competitors by a significant amount, the officials can order a review of that tractor with the board of directors.

21. Random dyno checks will take place at tech officials and directors discretion. Max 60hp in any class. If over 60hp all points accumulated that day will be forfeited. If unable to provide a dyno check due to a mechanical failure with pto, OVTPA tech committee can take necessary action to inspect for stock OEM components or modifications